

Specification Sheet

Product: Xylene

Parameters	Test Method	Result
Purity min%	ASTM D 4492	98.50%
Appearance @ 18.3 to 25.6°C	Visual	Clear liquid free of sediment
Colour	Pt-Co	Max. 20
Relative Density 15.6/15.6°C	ASTM D 4052	0.865 – 0.875
Distillation: IBP Deg C	ASTM D 850	136.0
Distillation: DP Deg C	ASTM D 850	143.0
Non Aromatic Hydrocarbons, percent by mass	ASTM D 4492	Max. 1.5
Benzene Cont, % w/w	ASTM D 4492	Max. 0.01
H ₂ S & Mercaptans	ASTM D 853	Absent
C ₉ + Aromatics, % w/w	ASTM D 4492	Max. 0.50
Flash Point Deg C	ASTM D 93	27

Note:

The information above is believed to be accurate and represents the best information currently available to us. However, we make no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. In no event shall AGR Enterprises be liable for any claims, losses, or damages of any third party or for lost profits or any special, indirect, incidental, consequential or exemplary damages, howsoever arising, even if AGR Enterprises has been advised of the possibility of such damages.